

Bitzer 4G.2 (x3) / 6F.2 (x1)

Specifications

Brand	Bitzer
Type	4G.2 (x3) / 6F.2 (x1)
Refrigerant	Freon
kW at +10°C/+40°C	465,2
kW at 0°C/+40°C	303,4
kW at -5°C/+40°C	268,6
kW at -10°C/+40°C	219,5
kW at -20°C/+40°C	140,9
kW at -30°C/+40°C	84
kW at -40°C/+40°C	43,8
Electromotor Specs	22 / 37
Unloaded Start	✓
Capacity Control	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Oil separator	✓
Remarks	# // 1x Compr. Bitzer 4G.2 y.o.b. 2007 // Electromotor 4G.2: 22 kW at 1480 RPM // Electromotor 6F.2: 37 kW at 1475 RPM
Remarks	R404a - R22 or other freon types



Package / Rack	✓
Sizes	3800x1350x1950 mm (LxWxH)
Stock	1

Description

Used Bitzer 4G.2 (x3) / 6F.2 (x1)

Used Bitzer 4G.2 (x3) / 6F.2 (x1) freon compressor rack, complete with unloaded start, capacity control, pressure safety switches, pressure gauges and oil separator. this unit has a cooling capacity of 465,2 kW at +10°C/+40°C.

Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and deliver after an industrial cleaning. *If requested we are happy to arrange your logistics.





