

Sabroe SMC 112 E MK3 package

Specifications

| Sabroe |
|-------------------------|
| SMC 112 E MK3 package |
| NH 3 (ammonia) |
| 1293,1 |
| 862,6 |
| 690,4 |
| 543,4 |
| 315,6 |
| 160 |
| 58,3 |
| 200 |
| ✓ |
| ✓ |
| ✓ |
| ✓ |
| ✓ |
| y.o.b. 2002 // |
| Electromotor: 200 kW at |
| 1480 RPM |
| 1 |
| 2900x1100x1600 mm |
| (LxWxH) |
| 1 |
| |



Description

Used Sabroe SMC 112 E MK3 package

Used Sabroe SMC 112 E MK3 package. Complete with a Sabroe SMC 112 E NH3 compressor. Schorch 50 Hz - 200 kW - 1480 RPM. OVUR 4113D oil seperator and capacity control. *Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment soley if it has passed our extensive quality test and after it has been cleaned industrially. *If requested we are happy to arrange your shipment.



Your partner for used commercial and industrial refrigeration equipment















Your partner for used commercial and industrial refrigeration equipment











Your partner for used commercial and industrial refrigeration equipment



| DK 8270 Højbjerg | Refrige | 2516.326 | |
|---|-----------------------|-------------------|-----|
| Beholder / Vessel / Beha | 71450 | ear 2002 | |
| Туре | OVUR 41 | 13D | |
| Beregningsnorm / Desigr Berechnungsnorm. | CODAP | | |
| Godkendelses no. Approval no. Abnahme nr. | HIDYORCOZOI | DNK / IV | |
| Side / Seite Medie / Media | Svøb / Shell / Mantel | Rør / Tube / Rohr | |
| Tilladeligt tryk Allowable pressure Zulässiger Druck Tilladeligt temp. | 29.07 | 1 | Bar |
| Tilladeligt temp. Allowable temperature Zulässiger Temperatur | 201 | 1 | •c |
| Volumen Volume | | | |