

Goedhart VC 82507

Specifications

Brand	Goedhart
Type	VC 82507
kW	24,7
Refrigerant	Freon
Number of Fans	2
Fin Space in mm	7
Defrosting	Electric
m ³ /h	13.560
Sizes	2310x980x720 mm (LxWxH)
Remarks	Fan: 450 WATTS / 1360 RPM / Ø = 500 mm
Stock	8



Description

Used Goedhart VC 82507

Used Goedhart VC 82507 // 2x Fans:
WOODS / 450 WATTS / 1360 RPM / Ø =
500 mm / 13560 m³/h



R404A										Refrigerant											
Type VCI	Type VCI		Type VCI		Type VCI		Type VCI		Type VCI		Type VCI		Type VCI		Type VCI		Type VCI		Type VCI		
	W	H	W	H	W	H	W	H	W	H	W	H	W	H	W	H	W	H	W	H	
4.14.0.7	4.0	2.8	3430	52	22	6	76	1156	670	620	500	756	578	15	15	20	20	20	20	20	20
4.14.0.7	5.1	3.8	3285	52	33	9	80	1156	770	620	600	756	578	12	15	19	20	20	20	20	20
4.14.0.7	6.1	4.8	3147	52	33	9	80	1156	870	620	600	756	578	12	15	19	20	20	20	20	20
4.14.0.7	5.5	4.1	5206	56	30	8	93	1256	670	720	500	856	628	12	22	19	22.5	22.5	22.5	22.5	22.5
4.14.0.7	6.5	4.968			30	8	93	1256	670	720	500	856	628	12	22	19	22.5	22.5	22.5	22.5	22.5
4.14.0.7	9.2	6.5	4754	56	61	16	116	1256	870	720	700	856	628	12	22	19	22.5	22.5	22.5	22.5	22.5
4.14.0.7	7.8	5.5	7387	63	38	10	115	1456	790	720	600	1056	728	12	22	19	22.5	22.5	22.5	22.5	22.5
4.14.0.7	10.3	7.073			38	10	115	1456	790	720	600	1056	728	12	22	19	22.5	22.5	22.5	22.5	22.5
4.14.0.7	12.4	8.9	6786	63	76	19	143	1456	990	720	800	1056	728	12	28	19	22.5	22.5	22.5	22.5	22.5
4.14.0.7	10.5	10.553			76	19	143	1456	990	720	800	1056	728	12	28	19	22.5	22.5	22.5	22.5	22.5
4.14.0.7	15.1	10.6	10195	63	84	21	166	1556	1010	920	800	1156	778	12	28	19	22.5	22.5	22.5	22.5	22.5
4.14.0.7	16.7	11.5	9864	63	112	28	193	1556	1110	920	900	1156	778	16	28	19	22.5	22.5	22.5	22.5	22.5
4.14.0.7	14.3	10.5	13095	63	76	11	203	1656	990	1120	700	1256	828	12	28	19	22.5	22.5	22.5	22.5	22.5
4.14.0.7	19.6	14.1	12734	63	114	29	206	1656	1100	1120	800	1256	828	16	35	19	22.5	22.5	22.5	22.5	22.5
4.14.0.7	23.9	19.384			152	40	243	1656	1110	1120	900	1256	828	16	35	19	22.5	22.5	22.5	22.5	22.5
4.24.0.7	8.0	5.6	6853	55	44	11	123	856	770	620	500	1456	928	12	22	19	22.5	22.5	22.5	22.5	22.5
4.24.0.7	7.0	7.6	8563	55	66	17	130	856	770	620	600	1456	928	12	22	19	22.5	22.5	22.5	22.5	22.5
4.24.0.7	12.0	6.285	95	55	66	17	130	856	890	720	700	1456	928	12	22	19	22.5	22.5	22.5	22.5	22.5
4.24.0.7	11.7	8.2	10405	59	60	15	151	2056	670	720	500	1656	1028	12	28	19	22.5	22.5	22.5	22.5	22.5
4.24.0.7	12.0	9.936			60	15	151	2056	670	720	500	1656	1028	12	28	19	22.5	22.5	22.5	22.5	22.5
4.24.0.7	18.3	13.2	9495	59	121	30	192	2056	870	720	700	1656	1028	16	28	19	22.5	22.5	22.5	22.5	22.5
4.24.0.7	15.9	11.0	6495	59	76	13	191	2456	990	720	600	2056	1228	16	28	19	22.5	22.5	22.5	22.5	22.5
4.25.0.7	20.2	14.9	14135	66	114	29	205	2456	890	720	700	2056	1228	16	35	19	22.5	22.5	22.5	22.5	22.5
4.25.0.7	26.7	17.8	18560	66	152	38	242	2456	990	720	800	2056	1228	16	35	19	22.5	22.5	22.5	22.5	22.5
4.25.0.7	21.966						247	2556	910	720	800	2256	1278	16	35	19	22.5	22.5	22.5	22.5	22.5

