

## Bitzer 4G.2 + 6G.2 cool/freeze unit

### Specifications

Brand	Bitzer
Type	4G.2 + 6G.2 cool/freeze unit
Refrigerant	Freon
kW at -5°C/+40°C	145.1
kW at -10°C/+40°C	119.3
kW at -20°C/+40°C	77.8
kW at -30°C/+40°C	47.4
kW at -40°C/+40°C	25.6
Unloaded Start	✓
Capacity Control	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Liquid receiver	✓
Oil separator	✓
Oil level system AC&R	✓
Liquid line filter drier	✓
Stock	1



### Description

#### Used Bitzer 4G.2 + 6G.2 cool/freeze unit

Used cool/freeze unit with an Bitzer 4G-20.2Y Semi-hermetic Reciprocating piston Compressor + an Bitzer 6G-2 Open-Type Reciprocating Compressor and electromotor with 30 kW at 1465 RPM and 1 electromotor with 18.5 kW at 1465 RPM, with liquid tank, oil separator, oil reservoir and Oil level system AC&R. Our capacity table is based on the used type of Freon. You can also use these compressors on alternative types of Freon. For all the other specs (if available), see the picture of the manufacturer model plate or the attached pdf file. \*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test,



warranty and industrial cleaning.

\*Optional we can also perform a new  
paint job and arrange the logistics.





