

Helpman LEX 30

Specifications

| | |
|-------------------|--|
| Brand | Helpman |
| Type | LEX 30 |
| kW | 36,5 |
| Refrigerant | Freon |
| Number of Fans | 4 |
| Fin Space in mm | 7 |
| Defrosting | None |
| m ³ /h | 23400 |
| Sizes | 3400x800x800 mm |
| Remarks | Diameter fan 50 cm |
| Remarks | capacity based on R22, can be used with alternate types of Freon |
| Volume | 51,1 dm ³ |
| Weight | 256 kg |
| Stock | 4 |



Description

Used Helpman LEX 30

Used blow-through Helpman LEX 30 evaporator with four ATB fans, diameter 50 cm. *All components of this used evaporator will be tested on good working, leak free condition (electro engines), coils, bearings) Choosing HOSBV means buying with warranty. We perform a industrial cleaning and rust spots will be covered. Also, we can arrange your shipment.



Nominal Capacities (kW)

| Cooler type | R 22 | R 134a | R 404A | For reference only | | |
|-------------------------|-------------|-------------|-------------|--------------------|--------|-------|
| | frosted DT1 | frosted DT1 | frosted DT1 | dry conditions DT1 | | |
| | | | | R22 | R 134a | R404A |
| Fin spacing 4 mm | | | | | | |
| LEX 2-4 | 1.5 | 1.3 | 1.5 | 1.3 | 1.1 | 1.3 |
| LEX 4-4 | 1.9 | 1.5 | 1.8 | 1.7 | 1.3 | 1.6 |
| LEX 6-4 | 2.8 | 2.4 | 2.8 | 2.4 | 2.1 | 2.5 |
| LEX 8-4 | 4.7 | 4.1 | 4.7 | 4.1 | 3.5 | 4.1 |
| LEX 10-4 | 4.7 | 4.4 | 4.8 | 4.1 | 3.8 | 4.2 |
| LEX12-4 | 5.9 | 5.6 | 6.2 | 5.1 | 4.9 | 5.4 |
| LEX 14-4 | 6.5 | 6.4 | 7.1 | 5.7 | 5.6 | 6.2 |
| LEX 16-4 | 8.7 | 8.4 | 9.3 | 7.5 | 7.3 | 8.1 |
| LEX 18-4 | 9.7 | 8.7 | 9.8 | 8.5 | 7.6 | 8.6 |
| LEX 20-4 | 12.8 | 10.8 | 12.7 | 11.2 | 9.4 | 11.0 |
| LEX 22-4 | 16.1 | 13.0 | 15.4 | 14.0 | 11.3 | 13.4 |
| LEX 24-4 | 20.0 | 16.1 | 19.2 | 17.4 | 14.0 | 16.7 |
| LEX 26-4 | 26.0 | 23.0 | 26.0 | 22.6 | 20.0 | 22.6 |
| LEX 28-4 | 32.8 | 29.0 | 33.2 | 28.5 | 25.2 | 28.9 |
| LEX 30-4 | 40.3 | 32.5 | 38.5 | 35.0 | 28.3 | 33.4 |
| Fin spacing 7 mm | | | | | | |
| LEX 2-7 | 1.3 | 1.2 | 1.3 | 1.1 | 1.0 | 1.2 |
| LEX 4-7 | 1.7 | 1.4 | 1.7 | 1.5 | 1.2 | 1.4 |
| LEX 6-7 | 2.5 | 2.2 | 2.5 | 2.2 | 1.9 | 2.2 |
| LEX 8-7 | 4.1 | 3.7 | 4.3 | 3.6 | 3.3 | 3.7 |
| LEX 10-7 | 3.7 | 3.6 | 4.0 | 3.2 | 3.2 | 3.5 |
| LEX 12-7 | 5.0 | 4.9 | 5.3 | 4.4 | 4.3 | 4.6 |
| LEX14-7 | 5.5 | 5.5 | 6.0 | 4.8 | 4.8 | 5.2 |
| LEX16-7 | 7.4 | 7.3 | 8.0 | 6.4 | 6.3 | 7.0 |
| LEX18-7 | 8.5 | 7.8 | 8.8 | 7.4 | 6.8 | 7.6 |
| LEX20-7 | 11.4 | 10.0 | 11.4 | 9.9 | 8.7 | 9.9 |
| LEX22-7 | 14.5 | 12.4 | 14.3 | 12.6 | 10.7 | 12.4 |
| LEX 24-7 | 18.1 | 15.6 | 17.8 | 15.7 | 13.5 | 15.5 |
| LEX 26-7 | 22.8 | 21.2 | 23.4 | 19.8 | 18.4 | 20.4 |
| LEX 28-7 | 28.5 | 26.5 | 29.3 | 24.8 | 23.0 | 25.5 |
| LEX 30-7 | 36.5 | 31.0 | 35.9 | 31.7 | 27.0 | 31.2 |